

MATERIAL SAFETY DATA SHEET

SECTION I - MATERIAL IDENTIFICATION AND INFORMATION

Manufacturer's Name: Ultra-Look Products, Inc.
3903 Progress Drive
Lakeland, FL 33811
Telephone Number: (888) 454-2038

Effective Date: July 7, 2008

Trade Name: Blue Ice Tire Dressing
Formula: PROPRIETARY

DOT CLASSIFICATION: NONE NEEDED

FOR CHEMICAL EMERGENCY

CALL INFOTRAC

1-800-535-5053

24Hrs. per day, 7 days per week

SECTION II - HAZARDOUS INGREDIENTS

NAMES OF HAZARDOUS INGREDIENTS: See CFR29*1910.1200 (i)-(13)

CHEMICAL/COMMON NAME	CAS#	PERCENTAGE	PEL-OSHA	TLV-ACGIH
Hexane, n-	110-54-3		500PPM	1800mg/m

THIS PRODUCT DOES NOT CONTAIN CARCINOGENS: (NTP, IARC, OSHA):

SECTION III - PHYSICAL DATA

PRODUCTS DESCRIPTION: Blue liquid with distinctive odor.

SOLUBILITY IN WATER: Insoluble

BOILING POINT: >160 F

FLASH POINT: (Method Used) 0.65 (PMCC) 18 F

SPECIFIC GRAVITY: 1 (Water = 1)

VAPOR PRESSURE (mmHg): 124 (mmHg)

VAPOR DENSITY (AIR=1): >1 (Air = 1)

SPECIFIC GRAVITY (WATER=1): 0.7

PERCENT VOLATILE BY VOLUME (%): >87.00

EVAPORATION RATE (WATER=1): <1 (Water = 1)

SECTION IV - FIRE & EXPLOSION HAZARD DATA

FLAMMABLE LIMITS: LEI-N/D UEL-N/D

EXTINGUISHING MEDIA: NOT CONSIDERED A FIRE HAZARD

THIS PRODUCT IS STABLE

SECTION V - REACTIVITY DATA

STABILITY: STABLE

CONDITIONS TO AVOID: CONTACT WITH ANY CHEMICAL LISTED IN MATERIAL TO AVOID.

MATERIAL TO AVOID: AVOID CONTACT WITH ACIDS AND STRONG OXIDIZERS SUCH AS PERMANGANATE, CHLORINE, ETC.

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

HAZARDOUS DECOMPOSITION PRODUCTS: NONE REPORTED

SECTION VI - HEALTH HAZARD DATA

POSSIBLE ROUTES OF ENTRY: INHALATION - SKIN -

ACUTE HEALTH HAZARD:

- (A) EYES-CAN CAUSE SEVERE IRRITATION, REDNESS, TEARING, BLURRED VISION.
- (B) SKIN-PROLONGED OR REPEATED CONTACT CAN CAUSE MODERATE IRRITATION, DEFATTING, DERMATITIS.
- (C) INHALATION-BREATHING OF DUST OR MIST CAN CAUSE MILD TO SEVERE IRRITATION OF NASAL OR RESPIRATORY PASSAGE.
- (D) INGESTION-CAN CAUSE GASTROINTESTINAL IRRITATION, NAUSEA, VOMITING AND DIARRHEA.

CHRONIC HEALTH HAZARD:

- (A) OVEREXPOSURE TO ALIPHATIC HYDROCARBONS (IN IT'S PURE STATE) HAS BEEN FOUND TO CAUSE ANEMIA, LIVER ABNORMALITIES, KIDNEY DAMAGE, LUNG DAMAGE AND BLOOD ABNORMALITIES IN LABORATORY ANIMALS.
- (B) INHALATION MAY INCREASE SUSCEPTIBILITY TO RESPIRATORY ILLNESS.

CONDITIONS AGGRAVATED BY EXPOSURE:

Preexisting skin, eye and respiratory disorders may be aggravated by exposure to product.

EMERGENCY FIRST AID PROCEDURES:

1. Skin - Immediately flush skin with lots of running water for at least 30 minutes. Remove contaminated clothing and shoes. Wash before reuse.
2. Eyes - Flush immediately with large quantities of running water for at least 15 minutes. Consult a physician.
3. Inhalation - If affected, remove individual to fresh air. If breathing is difficulty, administer oxygen. If breathing has stopped, give artificial respiration. Keep person warm, quiet and get medical attention.
4. Ingestion - Immediately give a lot of water and do not induce vomiting. Never give anything by mouth to an unconscious person. Get medical attention immediately.

SECTION VII - SYMPTOMS OF EXPOSURE

EYES: INTENSE PAIN WITH TISSUE DESTRUCTION

SKIN: POSSIBLE MODERATE IRRITATION

INGESTION: GASTRIC DISTRESS - NAUSEA - VOMITING - DIARRHEA

INHALATION: MILD IRRITATION

CONDITIONS AGGRAVATED BY EXPOSURE: NONE KNOWN

SECTION VIII - FIRST AID

SKIN: IF IRRITATION OCCURS, CEASE USING TEMPORARILY.

EYES: FLUSH EYE WITH WATER FOR 15 MINUTES. SEEK MEDICAL ATTENTION.

INHALATION: IF IRRITATION OCCURS, SEEK MEDICAL ATTENTION.

INGESTION: DRINK A LARGE AMOUNT OF WATER , DO NOT INDUCE VOMITING. GET IMMEDIATE MEDICAL ATTENTION.

SECTION IX - SPILL, LEAK AND DISPOSAL INFORMATION

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OF SPILLED:

Absorb the large spill on suitable absorbent. Small spills can be flushed down the drain with plenty of water.

WASTE DISPOSAL METHODS:

Dispose of according to local, state and federal regulation for Aliphatic Solvents.

SECTION X - SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION: AN APPROPRIATE NIOSH APPROVED HYDROCARBON CANISTER OR RESPIRATORY FOR ORGANIC VAPOR SHOULD BE WORN IF NEED.

VENTILATION: USE IN A WELL VENTILATED AREA. BELOW TLV (s)

PROTECTIVE EQUIPMENT REQUIRED: GLOVES - SOLVENT RESISTANT GLOVES SUCH AS NITRILE RUBBER, PVC, ETC.

SPECIAL: N/A

MECHANICAL (GENERAL): EXPLOSION PROOF

OTHER PROTECTIVE EQUIPMENT: EYE WASH AND QUICK DRENCH FACILITIES.

OTHER ENGINEERING CONTROLS: NONE KNOWN

WORK PRACTICES: EYE WASH FOUNTAIN AND SAFETY SHOWER SHOULD BE EASILY ACCESSIBLE. DISCARD PROPERLY SUCH ITEMS AS RAGS AND TRASH SOAKED WITH THE PRODUCT. PROVIDER ADEQUATE VENTILATION. HYGIENIC PRACTICES: AVOID CONTACT WITH EYES, SKIN AND CLOTHING. AVOID INHALATION OF PRODUCT VAPORS. WASH THOROUGHLY AFTER HANDLING AND BEFORE EATING, DRINKING, OR SMOKING. REMOVE CONTAMINATED CLOTHING PROMPTLY AND WASH THOROUGHLY BEFORE REUSED.

SECTION XI - HANDLING AND STORAGE

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:

- (1) Do not store under freezing conditions or above 120 degrees F.
- (2) Protect form physical damage and keep tightly closed.
- (3) Do not store near acids or acidic materials and oxidizers.
- (4) Keep away from heat, sparks and open flames.
- (5) Containers even those that have been emptied will retain product residue and vapors. Always obey hazard warnings.

MAINTENANCE PRECAUTIONS:

When working with FLAMMABLE materials electrically ground all equipment and use only non-sparking tools.

SECTION XII - SHIPPING INFORMATION

UN/NA #S, SECONDARY CONTAINER LABEL INFO NECESSARY OR SUGGESTED.